

PRZEDSIĘBIORSTWO USŁUGOWO REMONTOWE
REMODEX
ZAKŁAD BADAŃ I WDROŻEŃ PRZEMYSŁU MEBLARSKIEGO
Spółka z o.o.

Gruszczyn, ul. Leśna 12
62-006 Kobylnica

e-mail: biuro@remodex.com.pl
KRS 0000099068

tel./fax. 61 817-49-97
tel. kom. 601 391 825

SIGN: BW/JK/250/14

DATE: 2014-07-29

Order from: 2014-07-01

TEST REPORT No: 219/14/W

Safety requirements, strength and durability

1. *Name and type of article -*

Swivel office chair BORA H with armrests

2. *CLIENT -*

MJ DESIGN KRAMKOWSKI I HIPE
Spółka Jawna
WIENIEC, ul. Parkowa 29
87-880 BRZEŚĆ KUJAWSKI

3. *Documents identifying article -*

order + technical records.

This article was tested in accordance
with the test procedures described in:

PN-EN 1335-1:2004
PN-EN 1335-2:2009
PN-EN 1335-3:2009

TEST RESULTS:

POSITIVE

Test operator


.....
/M Sc. (Eng.) Jacek Konieczny

PREZES ZARZĄDU


mgr inż. Piotr Błaszczak

TEST REPORT contain 4 pages

The test results are only valid for the article tested.

This TEST REPORT shall not be reproduced except in full, without the written approval of the laboratory.

TEST REPORT No: 219/14/W

OFFICE WORK CHAIR - DIMENSION

Name and type of article: **Swivel office chair BORA H with armrests**

Producer (Applicant) – MJ DESIGN – Wieniec

Dimension in mm

point PN-EN	Dimension		req. PN-EN 1335-1		in article	
			min.	max.	min.	max.
SEAT						
6.1	seat height adjustment range	<i>a</i>	400 120	510 ⊗	480	610 ^{*/} 130
6.2	seat depth adjustment range	<i>b</i>	400 50	420 ⊗	350 ^{**/}	400 50
6.3	depth of seat surface	<i>c</i>	380	⊗	-	450
6.4	seat width	<i>d</i>	400	⊗	-	510
6.5	inclination of seat surface ²⁾ adjustment range	<i>e</i>	-2° 6°	-7° ⊗	-2° -	-8° 6°
BACK						
6.6	height of the back point support- ing point "S" above the seat sur- face ¹⁾	<i>f</i>	170 50	220 ⊗	190	270 ^{*/} 80
6.7	height of back pad adjustment range ¹⁾	<i>g</i>	220	⊗	-	570
6.9	back rest width	<i>i</i>	360	⊗	-	480
6.10	horizontal radius of the back rest	<i>k</i>	400	⊗	-	770
6.11	back rest inclination adjustment range	<i>l</i>	15°	⊗	91°	115° 24°
ARM REST						
6.12	length of arm rest	<i>n</i>	200	⊗	-	250
6.13	width of arm rest	<i>o</i>	40	⊗	-	50
6.14	height of arm rest above the seat ²⁾	<i>p</i>	200	250	-	225
6.15	distance from the front of the arm rests to the front edge of the seat surface ¹⁾	<i>q</i>	100	⊗	-	155
6.16	clear width between the arm rest	<i>r</i>	460	510	-	500
UNDERFRAME						
6.17	maximum offset of the under- frame (anti-stumbling-dimension)	<i>s</i>	⊗	415	-	375
6.18	stability dimension	<i>t</i>	195	⊗	-	235

⊗ - no requirement specified

*/ - it admits to receive more

**/ - it admits to receive less

¹⁾ - adjustment,

²⁾ - not adjustment

³⁾ - the inclination the surface of seat together with from inclination the back

Attention: The dimensions of chairs are in accordance with requirements of norm for type A.

SIGNED: 
LABORATORIUM

TEST REPORT No: 219/14/W

OFFICE FURNITURE. OFFICE WORK CHAIR

The name, symbol and the type of piece of furniture: Swivel office chair BORA H with armrests

SAFETY REQUIREMENTS:

point PN-EN	Test description	Requirement	Test results
4.1.1	burrs, sharp edges, open ends of tubes	inadmissible	positive
	shear and squeeze points	inadmissible	
4.1.2	movable and adjustable parts	they do not injuries	positive
4.1.3	connection of bearing parts	they do not get loosen	positive
4.1.4	parts lubricated to assist sliding	does not cause staining	positive

STABILITY:

No	Test description	Loading	Test results
1	Front edge overturning	mass – 27 kg	pass
2	Forward overturning	vertical force F_1 600 N horizontal force F_2 20 N	pass
3	Sideways overturning for chairs with arm rests	vertical force F_1 250 N vertical force F_2 350 N horizontal force F_3 20 N	pass
4	Rearwards overturning	vertical force F_1 600 N horizontal force F_2 192 N	pass
	Rearwards overturning of chairs with back rest inclination	number of discs 13	pass

SIGNED: 
LABORATORIUM

TEST REPORT No: 219/14/W

OFFICE FURNITURE. OFFICE WORK CHAIR

The name, symbol and the type of piece of furniture: **Swivel office chair BORA H with armrests**

STRENGTH and DURABILITY

No	Part of furniture		Loading	cycles	Re-quire-ment	Test results
1	Front edge seat		vertical force 1600 N	10	without defects	pass
2	- seat		vertical force 1600 N	10		pass
	- back		horizontal force 560 N			
3	Seat and back durability	point A	vertical force 1500 N	120000		pass
		point C	vertical force 1200 N	80000		pass
		point B	horizontal force 320 N			
		point J	vertical force 1200 N	20000		pass
		point E	horizontal force 320 N			
		point F	vertical force 1200 N	20000		pass
		point H	horizontal force 320 N			
		point D	vertical force 1100 N	20000		pass
4	arms		vertical force 750 N	5		pass
			vertical force 900 N			
			vertical force 450 N	5		pass
			horizontal force 400 N	10		pass
			force 400 N , angel $10^{\circ} \pm 1^{\circ}$ to the vertical	60000		pass
5	swivel test of the chair		seat loading p.A-60 kg , p.C-35kg	120000		pass
6	castor ^{*/}	resistance of rolling	force minimum 15 N	---		force - 18 N pass
		durability	seat loading p.A-110 kg	36000		pass

^{*/} - H-type castors

Attention: the admissible maximum loading of seat - **150 kg**.

SIGNED: 
LABORATORIUM